

# RANGER COUPLINGS MULTI DRILL / TABLE 10 / TABLE 16



Wide range couplings suitable for joining pipes with the same nominal diameter – which have the same or different OD's. Cast in ductile iron Grade 420/12 to BS 2789:1985.

PE coated to:

- provide maximum corrosion protection
- prevent chipping or gouging of the coating

Rubber seals are approved for potable water and are certified to "WRAS/BS6920".

Large diameter bolts manufactured to BS970:1991 Grade 070-M20 and PE coated, ensure greater torque for easier fitting and sealing.

NOMINAL PIPE SIZE		Outside Diameter Range (mm)	CLAMPS SUITABLE TO FIT				
INCHES	mm		Maxumim Pressure rating	Steel Pipe	PVC / HDPE Pipe	Asbestos (CID) Pipe	Asbestos (COD) Pipe
1½"	40mm	<b>48 - 60mm</b>	16 Bar	✓	✓	X	X
2"	50mm	<b>59 - 76mm</b>	16 Bar	✓	✓	X	✓
2 ½"	65mm	<b>72 - 85mm</b>	16 Bar	✓	✓	X	✓
3"	80mm	<b>74 - 90mm</b>	16 Bar	✓	✓	X	X
		<b>88 - 103mm</b>	16 Bar	✓	✓	X	✓
		<b>98 - 118mm</b>	16 Bar	✓	✓	X	X
4"	100mm	<b>108 - 128mm</b>	16 Bar	✓	✓	X	✓
		<b>135 - 160mm</b>	16 Bar	✓	✓	X	✓
5"	125mm	<b>150 - 170mm</b>	16 Bar	✓	✓	✓	X
		<b>159 - 182mm</b>	16 Bar	✓	✓	✓	✓
		<b>180 - 194mm</b>	16 Bar	✓	X	X	X
6"	150mm	<b>190 - 210mm</b>	16 Bar	X	✓	X	X
		<b>190 - 220mm</b>	16 Bar	✓	✓	✓	X
		<b>218 - 235mm</b>	16 Bar	✓	X	✓	✓
7"	175mm	<b>227 - 252mm</b>	16 Bar	✓	✓	✓	X
		<b>250 - 267mm</b>	16 Bar	✓	X	✓	✓
		<b>272-289mm</b>	16 Bar	✓	X	✓	✓
8"	200mm	<b>286 - 304mm</b>	16 Bar	X	X	✓	✓
		<b>302 - 318mm</b>	16 Bar	X	✓	X	X
		<b>315 - 332mm</b>	16 Bar	✓	✓	✓	X
9"	225mm	<b>322 - 339mm</b>	16 Bar	✓	X	✓	X
		<b>332 - 349mm</b>	16 Bar	X	X	✓	X
		<b>344 - 360mm</b>	16 Bar	✓	✓	X	✓
10"	250mm	<b>356 - 372mm</b>	12 Bar	✓	X	✓	X
		<b>374 - 391mm</b>	12 Bar	X	X	✓	X
		<b>391 - 407mm</b>	12 Bar	✓	✓	✓	X
12"	300mm	<b>401 - 417mm</b>	12 Bar	X	X	✓	X
		<b>417 - 437mm</b>	12 Bar	X	X	✓	✓
		<b>430 - 446mm</b>	12 Bar	X	X	✓	X
14"	350mm	<b>444 - 460mm</b>	12 Bar	✓	✓	✓	X
		<b>458 - 474mm</b>	12 Bar	X	X	✓	X
		<b>477 - 493mm</b>	12 Bar	X	X	✓	X
16"	400mm	<b>494 - 510mm</b>	12 Bar	✓	✓	✓	✓
		<b>509 - 523mm</b>	12 Bar	X	X	X	X
		<b>518 - 534mm</b>	12 Bar	X	X	✓	X
18"	450mm	<b>526 - 546mm</b>	12 Bar	X	✓	✓	X
		<b>556 - 572mm</b>	12 Bar	✓	X	✓	X
		<b>586 - 602mm</b>	12 Bar	X	X	✓	X
20"	500mm	<b>600 - 614mm</b>	12 Bar	✓	X	✓	X
		<b>614 - 630mm</b>	12 Bar	X	X	✓	X
		<b>630 - 646mm</b>	12 Bar	X	X	✓	X
24"	600mm	<b>646 - 662mm</b>	12 Bar	✓	X	✓	X
		<b>662 - 678mm</b>	12 Bar	X	X	✓	X
		<b>678 - 694mm</b>	12 Bar	X	X	✓	X