

JUNIOR COUPLINGS (CODE CFW)



Cascade junior couplings provide a quick, easy, and cost-effective solution for repairing larger breaks in smaller diameter pipes. It provides a full circumference seal around the pipe. Available in sizes to suit galvanised and copper pipe from 1/2" (15mm) to 1 1/4" (32mm).

Junior Couplings Full Circle Gasket - Galvanized Pipe

Nominal Pipe Size	Outside Diameter	Part Number	Length	Weight
15mm	21.3mm	CFW 15mmG-3	75mm	0.25 kgs
20mm	26.7mm	CFW 20mmG-3	75mm	0.27 kgs
25mm	33.4mm	CFW 25mmG-3	75mm	0.29 kgs
32mm	42.2mm	CFW 32mmG-3	75mm	0.35 kgs

Junior Couplings Full Circle Gasket - Copper Pipe

Nominal Pipe Size	Outside Diameter	Part Number	Length	Weight
15mm	12.7mm	CFW 15mmC-3	75mm	0.22 kgs
20mm	19.05mm	CFW 20mmC-3	75mm	0.25 kgs
25mm	25.4mm	CFW 25mmC-3	75mm	0.27 kgs
32mm	31.75mm	CFW 32mmC-3	75mm	0.29 kgs
40mm	38.1mm	CFW 40mmC-3	75mm	0.32 kgs

Junior Coupling Installation instruction

Before Fitting: Clean the pipe where the clamp is to be fitted. Position the clamp so that the holes on the pipe are in the centre of the clamp. Mark the position on the pipe at each end of the clamp. Remove the clamp from the pipe. Apply a suitable plumbing lubricant smoothly on the whole area to be covered by the clamp Junior

Coupling (code CFW)

Unhitch the bolt head, slide gasket out and wrap around leak. Spread lugs open, snap into position over the gasket, tighten to 20-25Nm, making sure that the armour plate's centring nipples are positioned between the clamp's ends. Repair is complete.