

FLANGE ADAPTERS - MULTI RANGE



For use in joining pipes within a range OD's to flanges. Cast in ductile iron Grade 420/12 to BS2789:1985. PE coated to:

- provide maximum corrosion protection
- prevent chipping or gouging of the coating

Rubber seal is approved for potable water and certified to "WRAS/BS6920". Large diameter bolts manufactured to BS970:1991 Grade 070-M20 and PE coated.

16 BAR WP - FUSION BONDED EPOXY COATED

NOMINAL PIPE SIZE		Outside Diameter Range (mm)	Flange Range Compatibility			
INCHES	mm		Maximum Pressure rating	TD	T10	T16
2"	50mm	48 - 60mm	16 Bar	✓	✓	✓
2"	50mm	59 - 76mm	16 Bar	✓	✓	✓
3"	80mm	74 - 90mm	16 Bar	✓	✓	✓
3"	80mm	88 - 103mm	16 Bar	✓	✓	✓
4"	100mm	98 - 118mm	16 Bar	✓	✓	✓
		108 - 108mm	16 Bar	✓	✓	✓
6"	150mm	150 - 170mm	16 Bar	✓	✓	✓
		159-182mm	16 Bar	✓	✓	✓
7"	175mm	190 - 220mm	16 Bar	✓	✓	✓
8"	200mm	218 - 235mm	16 Bar	✓	✓	✓
9"	225mm	235 - 252mm	16 Bar	X	✓	✓
10"	250mm	250 - 267mm	16 Bar	X	✓	✓
		272 - 289mm	16 Bar	X	✓	✓
12"	300mm	302 - 318mm	16 Bar	X	✓	✓
		315 - 332mm	16 Bar	X	✓	✓
		332 - 349mm	16 Bar	X	✓	✓
14"	350mm	344 - 360mm	16 Bar	X	✓	✓
6"	400mm	391 - 407mm	16 Bar	X	✓	✓
18"	450mm	444 - 460mm	16 Bar	X	✓	✓
20"	500mm	494 - 510mm	16 Bar	X	✓	✓